



C	SHAFT FLAT ADDED	RDS
D	ADJUSTMENT INSTRUCTIONS ADDED	JBJ
E	LENGTHS WERE 43 / 52	RDS
F	2 WIRE -20 mA ADDED	JHF
G	GLAND ADDED	JHF
H	GLAND DIM , 2 WIRE LENGHT 50	RDS
J	REDRAWN WITH SERVO OPTION	JHF
K	SHORT GLAND ADDED	JHF
L	TITLE WAS P500,P502 & P503	JHF
M	SPRING STOPS ADDED	RDS

SPRING RETURN UNITS HAVE PHYSICAL STOPS AT ±55° AVAILABLE ON UNITS WITH RANGES UPTO ±50° UNSPRUNG UNITS HAVE NO STOPS

CHECKED AT REV. M

RDS

POSITEK

LIMITED

F	4/03/97	MATERIAL SEE NOTE 1	X ±0.4 X.X ±0.2 X.XX ±0.1 ALL DIMS mm
G	09/05/97		
H	3/9/97		
J	4/12/98		
K	8/12/98		
L	06/09/99	DESCRIPTION RIPS P500 ROTARY POSITION SENSOR	
M	15/2/00	SCALE 10mm	DRAWING NUMBER P500-11 REV M
		SHEET 1 OF 1	