

# Positek

RIPS® SERIES P501			Part Number Coding					Basic price is for following specifications
P501			Travel	A	Blank	Cable Length	Option 1	Option 2
<b>Miniature Rotary Sensor</b>								
<b>Travel</b>								
degrees rotation	30° to 140°	Value						
<b>Electrical Interface Options</b>								
Input	Output							
+ 5V dc nom.± 0.5V	0.5 to 4.5V dc ratiometric	A						
<b>Adjusts not available</b>								
<b>Cable</b>								
Cable - Axial	Please specify cable length in cm.	Lxx	eg. L2000 specifies 20 metres of cable.					
<b>OPTIONS</b>								
<b>Shaft Type</b>			<b>Option 1</b>					
Standard plain with flat		N						
Tongue with spring clip		P						
<b>Lid Type</b>			<b>Option 2</b>					
Please select one.								
Lid with heatshrink and boot		T						
Lid with pins only	Units with Zero cable length only (L0)	U						

**Code**

Electrical            **A** 5V input

Cable                **L50** 50 cm screened cable

Shaft                 **N** Plain shaft with flat

Lid                    **T** Lid with heatshrink & boot

**Travel (customer specified)**  
any angle between 30° and 140°

**For more information, please contact:**  
 Everight Precision Technologies Corporation  
 102 Commerce Dr., Unit 8, Moorestown, NJ 08057  
 www.everightsensors.com info@everightsensors.com  
 phone: 856-727-9500 fax: 610-672-9663