


DRAWING NOT TO BE CHANGED WITHOUT REFERENCE TO THE CHANGE PROCEDURE.
CHANGES TO PARTS USED IN INTRINSICALLY SAFE PRODUCT MUST BE APPROVED BY THE AUTHORISED PERSON
THIS IS AN UNCONTROLLED PRINT AND WILL NOT BE UPDATED

A	FIRST ISSUE	RDS
B	REDRAWN WITH NEW OPTIONS	JHF
C	SHAFT TOL +0/-0.04 ADDED	JHF

CHECKED AT REV.	C
RDS	

SUPPLY OPTIONS

- A 5V SUPPLY 0.4 TO 4.5V O/P
- C 24V SUPPLY 0.5 TO 9.5V O/P
- D ±15V SUPPLY ±10V O/P
- E 2 WIRE 4 TO 20 mA
- F 3 WIRE 4 TO 20 mA SINK
- H 3 WIRE 4 TO 20 mA SOURCE



A	23/2/98		MATERIAL	X ±0.4
B	04/01/99		SEE NOTE 1	X.X ±0.2
C	26/08/99			X.XX ±0.1
DESCRIPTION				ALL DIMS mm
RIPS				
ROTARY POSITION SENSOR				
SMALL ANGLE 2° TO 30°				
SCALE	10mm	DRAWING NUMBER	P502-11	REV C
		SHEET	1	OF 1